**Product Data Sheet** 

Edition: January 2018

Version: 01

Sikadur<sup>®</sup> Aggregates

## Sikadur<sup>®</sup> Aggregates

## Selected Quartz Sand Gradings for Special Flooring Application

	<u></u>		<u> </u>	
		Grading	Bulk Density	Packaging
Sikadur <sup>®</sup> -504	Component C (filler) for self-levelling Sikafloor® Products  • Sikafloor® - 161 (Scratch coat)  • Sikafloor® - 263  • Sikafloor® - 325  • Sikafloor® - 326  • Sikafloor® - 300  • Sikafloor® - 330  • Sikafloor® - 262(AS)  • Sikafloor® - 381(AS)	0.08 – 0.2 mm	1.5 Kg/Lt	25 Kg Bag
Sikadur <sup>®</sup> -505	Broadcasting aggregates (not Component C) for Sikafloor® and Sikagard® products  Such as:  Sikafloor®- 81 Epocem Sikafloor®- 82 Epocem Sikafloor®- 161 Sikafloor®- 264 Sikafloor®- 264 SG Sikafloor®- 264 TD Sikafloor®- 325 Sikafloor®- 326 Sikafloor®- 350 Elastic	0.1 – 0.5 mm	1.4 Kg/Lt	25 Kg Bag
Sikadur <sup>®</sup> -506	Component C (aggregates) for Mortar screeds for Sikafloor® products such as:  • Sikafloor®- 161  • Sikafloor®- 264	Combination of different gradings 0.1 - 1.2 mm	1.8 Kg/Lt	25 Kg Bag
Sikadur <sup>®</sup> -507	Broadcasting aggregates (not Component C) for Sikafloor® products such as:  • Sikafloor®- 81 Epocem • Sikafloor®- 82 Epocem • Sikafloor®- 161 • Sikafloor®- 264 • Sikafloor®- 264 SG • Sikafloor®- 264 TD • Sikafloor®- 325 • Sikafloor®- 326 • Sikafloor®- 350 Elastic	0.3 – 0.7 mm	1.5 Kg/Lt	25 Kg Bag
Sikadur <sup>®</sup> -508	Broadcasting aggregates (not Component C) for :  • Sikafloor®- 2430	0.1 – 0.3 mm	1.5 Kg/Lt	25 Kg Bag
Sikadur <sup>®</sup> -509	Coarse broadcasting aggregates (not component C) for Sikafloor® and Sikagard® products ( See Sikadur®-505 & 507)	0.7 – 1.2 mm	1.5 Kg/Lt	25 Kg Bag
Sikadur <sup>®</sup> -513	Component C (filler) for self-levelling Sikafloor® 263 SL (5mm thick application)	0.3 – 1.2 mm	1.5 Kg/Lt	18 Kg Bag



Value Base	All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.	
Local Restrictions	Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.	
Health and Safety Information	For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet containing physical, ecological, toxicological and other safety-related data.	
Legal Notice	The information, and, in particular, the recommendations relating to the application and end- use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.	

All products are manufactured under a management system certified to conform to the requirements of the quality, environmental and occupational health & safety standards ISO 9001, ISO 14001 and OHSAS 18001.



Sika Abyssinia Chemicals Manufacturing PLC Sebeta, Welete 500m on the Street in front of TOTAL Gas Station P.O. Box 1596-1110, Ethiopia

Phone: +251 113679748 +251 116182605 e-mail: sika@et.sika.com

Website: www.eth.sika.com